

Description	Beger Primer Pro 100, acrylic alkali resisting primer is high quality emulsion paint for priming masonry, which the surface to blocked alkali and efflorescence. No added lead and no added mercury for health and environmental safe.		
Feature and Benefits	* Easy to apply, give smooth appearance. * Excellent water and alkali resistance. * Good resistance to fungus mildew and mold attack.		
Properties for Use	Beger Primer Pro 100 suitable for decorative interior and exterior building, cement, concrete, brick, plaster, walls and protective alkali resisting primer for priming masonry surfaces.		
Film Thickness and Spreading Rate	Minimum	Maximum	Typical
* Dry film thickness (microns)	0	0	0
* Wet film thickness (microns)	0	0	0
* Theoretical coverage rate (m ² /U.S.Gallon/coat)	35	40	Actual consumption rate depends on application method and surface condition.
Physical Properties	* Vehicle type : Acrylic Primer * Finish : Matt * Colour : White * Solid by volume : - * Dry time (@25°C, 30 mm.DFT) Touch dry : 30 minutes Recoat : 2 - 4 hours Dry to handle : -		
Application Method	* Tool : Brush, roller or spray gun. * Thinner : Clean water. * Condition during application : The moisture content in the concrete should not exceed 14%. : Concrete and masonry cure at least 30 days before coating. : Application by brush or roller dilute with 10 - 15% clean water by volume.		
Application System	* Surface preparation : Surface should be dry and clean. : Remove completely all dirt, grease, oil, water or any contaminated by washing surface with suitable cleaner. : Repair all surface imperfections. Before application, fill and seal hairline cracks by working a generous amount of material into void. Cracks and gaps wider than 2.0 - 10.0 mm. should be filled with acrylic sealant. Use Beger Acrylic Wall Filler #F-200 for cracks and gaps with less than 0.3 - 1.0 mm. width. : Surface with fungus, mold and mildew growth must be cleaned off and follow by the treatment of fungicidal wash Beger MouldFree #M-001. * Typical paint system : New masonry substrate * Primer : Beger Primer Pro 100 1 - 2 coats * Top coat : Beger 100%Acrylic Emulsion Paint 2 - 3 coats		
Storage	: The product must be stored in accordance with national regulations. Storage conditions are to keep the containers in a dry, cool, well ventilated space and away form source of heat an ignition. : Containers must be kept tightly closed. : 36 months at ambient.		
Health and safety	: Use under well ventilated conditions. : Do not breathe or inhale mist. : Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. : Eyes should be well flushed with water and medical attention sought immediately.		
Precaution	: Keep out of reach of children.		
Reference Standard	: -		
Packing Size	: 1 Gallon, 2.5 Gallons and 5 Gallons.		

DISCLAIMER

The information in this data sheet is given to the best of our knowledge based on laboratory testing and practical experience. However, as the product is often used under conditions beyond our control, We cannot guarantee anything but the quality of the product itself. We reserve the right to change the given data without notice.